

D2
D3
D4
D5
D6
D7
D8
D9
D10
D11
D12
D13
D14
D15
D16
D17
D18
D19
D20
D21
D22
D23
D24
D25
D26
D27
D28
D29
D30
D31
D32
D33
D34
D35
D36
D37
D38
D39
D40
D41
D42
D43
D44
D45
D46
D47
D48
D49
D50
D51
D52
D53
D54
D55
D56
D57
D58
D59
D60
D61
D62
D63
D64
D65
D66
D67
D68
D69
D70
D71
D72
D73
D74
D75
D76
D77
D78
D79
D80
D81
D82
D83
D84
D85
D86
D87
D88
D89
D90
D91
D92
D93
D94
D95
D96
D97
D98
D99
D100
D101
D102
D103
D104
D105
D106
D107
D108
D109
D110
D111
D112
D113
D114
D115
D116
D117
D118
D119
D120
D121
D122
D123
D124
D125
D126
D127
D128
D129
D130
D131
D132
D133
D134
D135
D136
D137
D138
D139
D140
D141
D142
D143
D144
D145
D146
D147
D148
D149
D150
D151
D152
D153
D154
D155
D156
D157
D158
D159
D160
D161
D162
D163
D164
D165
D166
D167
D168
D169
D170
D171
D172
D173
D174
D175
D176
D177
D178
D179
D180
D181
D182
D183
D184
D185
D186
D187
D188
D189
D190
D191
D192
D193
D194
D195
D196
D197
D198
D199
D200
D201
D202
D203
D204
D205
D206
D207
D208
D209
D210
D211
D212
D213
D214
D215
D216
D217
D218
D219
D220
D221
D222
D223
D224
D225
D226
D227
D228
D229
D230
D231
D232
D233
D234
D235
D236
D237
D238
D239
D240
D241
D242
D243
D244
D245
D246
D247
D248
D249
D250
D251
D252
D253
D254
D255
D256
D257
D258
D259
D260
D261
D262
D263
D264
D265
D266
D267
D268
D269
D270
D271
D272
D273
D274
D275
D276
D277
D278
D279
D280
D281
D282
D283
D284
D285
D286
D287
D288
D289
D290
D291
D292
D293
D294
D295
D296
D297
D298
D299
D300
D301
D302
D303
D304
D305
D306
D307
D308
D309
D310
D311
D312
D313
D314
D315
D316
D317
D318
D319
D320
D321
D322
D323
D324
D325
D326
D327
D328
D329
D330
D331
D332
D333
D334
D335
D336
D337
D338
D339
D340
D341
D342
D343
D344
D345
D346
D347
D348
D349
D350
D351
D352
D353
D354
D355
D356
D357
D358
D359
D360
D361
D362
D363
D364
D365
D366
D367
D368
D369
D370
D371
D372
D373
D374
D375
D376
D377
D378
D379
D380
D381
D382
D383
D384
D385
D386
D387
D388
D389
D390
D391
D392
D393
D394
D395
D396
D397
D398
D399
D400
D401
D402
D403
D404
D405
D406
D407
D408
D409
D410
D411
D412
D413
D414
D415
D416
D417
D418
D419
D420
D421
D422
D423
D424
D425
D426
D427
D428
D429
D430
D431
D432
D433
D434
D435
D436
D437
D438
D439
D440
D441
D442
D443
D444
D445
D446
D447
D448
D449
D450
D451
D452
D453
D454
D455
D456
D457
D458
D459
D460
D461
D462
D463
D464
D465
D466
D467
D468
D469
D470
D471
D472
D473
D474
D475
D476
D477
D478
D479
D480
D481
D482
D483
D484
D485
D486
D487
D488
D489
D490
D491
D492
D493
D494
D495
D496
D497
D498
D499
D500
D501
D502
D503
D504
D505
D506
D507
D508
D509
D510
D511
D512
D513
D514
D515
D516
D517
D518
D519
D520
D521
D522
D523
D524
D525
D526
D527
D528
D529
D530
D531
D532
D533
D534
D535
D536
D537
D538
D539
D540
D541
D542
D543
D544
D545
D546
D547
D548
D549
D550
D551
D552
D553
D554
D555
D556
D557
D558
D559
D560
D561
D562
D563
D564
D565
D566
D567
D568
D569
D570
D571
D572
D573
D574
D575
D576
D577
D578
D579
D580
D581
D582
D583
D584
D585
D586
D587
D588
D589
D590
D591
D592
D593
D594
D595
D596
D597
D598
D599
D600
D601
D602
D603
D604
D605
D606
D607
D608
D609
D610
D611
D612
D613
D614
D615
D616
D617
D618
D619
D620
D621
D622
D623
D624
D625
D626
D627
D628
D629
D630
D631
D632
D633
D634
D635
D636
D637
D638
D639
D640
D641
D642
D643
D644
D645
D646
D647
D648
D649
D650
D651
D652
D653
D654
D655
D656
D657
D658
D659
D660
D661
D662
D663
D664
D665
D666
D667
D668
D669
D670
D671
D672
D673
D674
D675
D676
D677
D678
D679
D680
D681
D682
D683
D684
D685
D686
D687
D688
D689
D690
D691
D692
D693
D694
D695
D696
D697
D698
D699
D700
D701
D702
D703
D704
D705
D706
D707
D708
D709
D710
D711
D712
D713
D714
D715
D716
D717
D718
D719
D720
D721
D722
D723
D724
D725
D726
D727
D728
D729
D730
D731
D732
D733
D734
D735
D736
D737
D738
D739
D740
D741
D742
D743
D744
D745
D746
D747
D748
D749
D750
D751
D752
D753
D754
D755
D756
D757
D758
D759
D760
D761
D762
D763
D764
D765
D766
D767
D768
D769
D770
D771
D772
D773
D774
D775
D776
D777
D778
D779
D780
D781
D782
D783
D784
D785
D786
D787
D788
D789
D790
D791
D792
D793
D794
D795
D796
D797
D798
D799
D800
D801
D802
D803
D804
D805
D806
D807
D808
D809
D810
D811
D812
D813
D814
D815
D816
D817
D818
D819
D820
D821
D822
D823
D824
D825
D826
D827
D828
D829
D830
D831
D832
D833
D834
D835
D836
D837
D838
D839
D840
D841
D842
D843
D844
D845
D846
D847
D848
D849
D850
D851
D852
D853
D854
D855
D856
D857
D858
D859
D860
D861
D862
D863
D864
D865
D866
D867
D868
D869
D870
D871
D872
D873
D874
D875
D876
D877
D878
D879
D880
D881
D882
D883
D884
D885
D886
D887
D888
D889
D890
D891
D892
D893
D894
D895
D896
D897
D898
D899
D900
D901
D902
D903
D904
D905
D906
D907
D908
D909
D910
D911
D912
D913
D914
D915
D916
D917
D918
D919
D920
D921
D922
D923
D924
D925
D926
D927
D928
D929
D930
D931
D932
D933
D934
D935
D936
D937
D938
D939
D940
D941
D942
D943
D944
D945
D946
D947
D948
D949
D950
D951
D952
D953
D954
D955
D956
D957
D958
D959
D960
D961
D962
D963
D964
D965
D966
D967
D968
D969
D970
D971
D972
D973
D974
D975
D976
D977
D978
D979
D980
D981
D982
D983
D984
D985
D986
D987
D988
D989
D990
D991
D992
D993
D994
D995
D996
D997
D998
D999
D1000

120. (Amended) An apparatus comprising a copper oxide having a T_c greater than 26°K carrying a superconducting current said copper oxide is maintained at a temperature less than said T_c .

124. (Amended) A device comprising a composition of matter having a T_c greater than 26°K carrying a superconducting current, said composition comprising at least one each of a Group III B element, an alkaline earth, and copper oxide said device is maintained at a temperature less than said T_c .

130. (Added) A superconductive apparatus comprising a composition having a transition temperature greater than 26°K, the composition including a rare earth or Group III B element, a transition metal element capable of exhibiting multivalent states and oxygen, including at least one phase that exhibits superconductivity at temperature in excess of 26°K, a means for maintaining said composition at said temperature to exhibit said superconductivity and means for passing an electrical superconducting current through said composition which exhibiting said superconductivity.

131. (Added) The combination of claim 15, where said additional element is a rare earth or Group III B element.

132. (Added) The combination of claim 12, where said composition includes a substantially perovskite superconducting phase.

133. (Added) The superconducting apparatus of claim 27, where said substituted Cu-oxide includes a rare earth or Group III B element.

134. (Added) The combination of claim 71, where said mixed copper oxide further includes a rare earth or Group III B element.

135. (Added) A combination, comprising:

DDP added

a mixed copper oxide composition including an alkaline earth element (AE) and a rare earth or Group III B element (RE), said composition having a substantially layered crystalline structure and multi-valent oxidation states, said composition exhibiting a substantially zero resistance to the flow of electrical current therethrough when in a superconducting state at a temperature in excess of 26°K, said mixed copper oxide having a superconducting onset temperature greater than 26°K and,

sub g1

electrical means for passing an electrical superconducting current through said composition when said composition exhibits substantially zero resistance at a temperature greater than 26°K and less than said onset temperature.

136. (Added) The combination of claim 77, where said crystalline structure is substantially perovskite.

137. (Added) An apparatus comprising:

sub g13

¹¹² forming a composition including a transition metal, a rare earth or Group III B element, an alkaline earth element, and oxygen, where said composition is a mixed transition metal oxide having a non-stoichiometric amount of oxygen therein and exhibiting a

superconducting state at a temperature greater than 26°K,

means for maintaining said composition in said superconducting state at a temperature greater than 26°K, and less than said superconducting onset temperature, and

means for passing an electrical current through said composition while said composition is in said superconducting state.

138. (Added) The apparatus of claim 93, where said copper oxide material exhibits a substantially layered crystalline structure.

139. (Added) A superconductive apparatus for causing electric-current flow in a superconductive state at a temperature in excess of 26°K, comprising:

(a) a superconductor element made of a superconductive composition, the superconductive composition consisting essentially of a copper-oxide compound having a substantially layered perovskite crystal structure, the composition having a superconductor transition temperature T_c of greater than 26°K;

(b) means for maintaining the superconductor element at a temperature above 26°K and below the superconductor transition temperature T_c of the superconductive composition; and

(c) means for causing an electric current to flow in the superconductor element.

140. (Added) A superconductive apparatus for conducting an electric current essentially without resistive losses, comprising:

DP added
put 7'
(a) a superconductor element made of a superconductive composition, the superconductive composition consisting essentially of a copper-oxide compound having a substantially layered perovskite crystal structure, the copper-oxide compound including at least one rare-earth or Group III B element and at least one alkaline-earth element, the composition having a superconductive/resistive transition defining a superconductive/resistive-transition temperature range between an upper limit defined by a transition-onset temperature T_c and a lower limit defined by an effectively-zero-bulk-resistivity intercept temperature $T_{p=0}$, the transition-onset temperature T_c being greater than 26°K;

(b) means for maintaining the superconductor element at a temperature below the effectively-zero-bulk-resistivity intercept temperature $T_{p=0}$ of the superconductive composition; and

(c) means for causing an electric current to flow in the superconductor element.

141. (Added) An apparatus comprising a transition metal oxide having a phase therein which exhibits a superconducting state at a critical temperature in excess of 26°K,

a temperature controller maintaining the temperature of said material at a temperature less than said critical temperature to produce said superconducting state in said phase, and

a current source passing an electrical supercurrent through said transition metal oxide while it is in said superconducting state.

142. (Added) The apparatus of claim 141, where said transition metal oxide is comprised of a transition metal capable of exhibiting multivalent states.

143. (Added) The apparatus of claim 141, where said transition metal oxide is comprised of a Cu oxide.

DF added
144. (Added) An apparatus comprising:

pub 91
a composition including a transition metal, a rare earth or rare earth-like element, an alkaline earth element, and oxygen, where said composition is a mixed transition metal oxide having a non-stoichiometric amount of oxygen therein and exhibiting a superconducting state at a temperature greater than 26°K,

a temperature controller maintaining said composition in said superconducting state at a temperature greater than 26°K, and

a current source passing an electrical current through said composition while said composition is in said superconducting state.

145. (Added) The method of claim 144, where said transition metal is copper.

146. (Added) A method, including the steps of:

a composition exhibiting a superconductive state at a temperature in excess of 26°K,

a temperature controller maintaining said composition at a temperature in excess of 26°K at which temperature said composition exhibits said superconductive state, and

a current source passing an electrical current through said composition while said composition is in said superconductive state.

147. (Added) The method of claim 146, where said composition is comprised of a metal oxide.

148. (Added) ^{method} The metal of claim 146, where said composition is comprised of a transition metal oxide.

149. (Added) A superconductive apparatus for causing electric current flow in a superconductive state at a temperature in excess of 26°K, comprising:

(a) a superconductor element made of a superconductive composition, the superconductive composition consisting essentially of a copper-oxide compound having a layer-type perovskite-like crystal structure, the

composition having a superconductor transition temperature T_c of greater than 26°K;

(b) a temperature controller maintaining the superconductor element at a temperature above 26°K and below the superconductor transition temperature T_c of the superconductive composition; and

(c) causing an electric current to flow in the superconductor element.

Dep't added
150. (Added) The superconductive apparatus according to claim 149 in which the copper-oxide compound of the superconductive composition includes at least one rare-earth or rare-earth-like element and at least one alkaline-earth element. *112*

Pub 3'
151. (Added) The superconductive apparatus according to claim 150 in which the rare-earth or rare-earth-like element is lanthanum.

152. (Added) The superconductive apparatus according to claim 150 in which the alkaline-earth element is barium.

153. (Added) The superconductive apparatus according to claim 149 in which the copper-oxide compound of the superconductive composition includes mixed valent copper ions.

154. (Added) The superconductive apparatus according to claim 153 in which the copper-oxide compound includes at least one element in a nonstoichiometric atomic proportion.

155. (Added) The superconductive apparatus according to claim

154 in which oxygen is present in the copper-oxide compound in a nonstoichiometric atomic proportion.

156. (Added) A superconductive apparatus for conducting an electric current essentially without resistive losses, comprising:

*DP
Cred*

(a) a superconductor element made of a superconductive composition, the superconductive composition consisting essentially of a copper-oxide compound having a layer-type perovskite-like crystal structure, the copper-oxide compound including at least one rare-earth or rare-earth-like element and at least one alkaline-earth element, the composition having a superconductive/resistive-transition defining a superconductive/resistive-transition temperature range between an upper limit defined by a transition-onset temperature T_c and a lower limit defined by an effectively-zero-bulk-resistivity intercept temperature $T_{p=0}$, the transition-onset temperature T_c being greater than 26°K;

*Pub
3'*

(b) a temperature controller maintaining the superconductor element at a temperature below the effectively-zero-bulk-resistivity intercept temperature $T_{p=0}$ of the superconductive composition; and

(c) a current source causing an electric current to flow in the superconductor element.

157. (Added) The superconductive apparatus according to claim 156 in which the rare-earth or rare-earth-like element is lanthanum.

158. (Added) The superconductive apparatus according to claim 156 in which the alkaline-earth element is barium.

159. (Added) The superconductive apparatus according to claim 156 in which the copper-oxide compound of the superconductive composition includes mixed valent copper ions.

160. (Added) The superconductive apparatus according to claim 159 in which the copper-oxide compound includes at least one element in a nonstoichiometric atomic proportion.

161. (Added) The superconductive apparatus according to claim 160 in which oxygen is present in the copper-oxide compound in a nonstoichiometric atomic proportion.

162. (Added) An apparatus including copper oxide having a phase therein which exhibits a superconducting state at a critical temperature in excess of 26°K;

a temperature controller maintaining the temperature of said material at a temperature less than said critical temperature to produce said superconducting state in said phase;

a current source passing an electrical supercurrent through said copper oxide while it is in said superconducting state;

said copper oxide includes at least one element selected from the group consisting of a Group II A element, a rare earth element and a Group III B element.

163. (Added) An apparatus comprising the steps of:

*Sub
275
child*
a composition including copper, oxygen and any element selected from the group consisting of a Group II A element, a rare earth element and a Group III B element, where said composition is a mixed copper oxide having a non-stoichiometric amount of oxygen therein and exhibiting a superconducting state at a temperature greater than 26°K;

a temperature controller maintaining said composition in said superconducting state at a temperature greater than 26°K; and

*Sub
276
child*
a current source passing an electrical current through said composition while said composition is in said superconducting state.

164. (Added) An apparatus comprising:

a composition exhibiting a superconductive state at a temperature in excess of 26°K;

a temperature controller maintaining said composition at a temperature in excess of 26°K at which temperature said composition exhibits said superconductive state;

*Sub
277
child*
a current source passing an electrical current through said composition while said composition is in said superconductive state; and

said composition including a copper oxide and an element selected from the group consisting of Group II A element, a rare earth element and a Group III B element.

165. (Added) An apparatus for causing electric-current flow in a superconductive state at a temperature in excess of 26°K, comprising:

(a) a superconductor element made of a superconductive composition, the superconductive composition consisting essentially of a copper-oxide compound having a layer-type perovskite-like crystal structure, the composition having a superconductive transition temperature T_c of greater than 26°K, said superconductive composition includes at least one element selected from the group consisting of a Group II A element, a rare earth element; and a Group III B element;

(b) a temperature controller maintaining the superconductor element at a temperature above 26°K and below the superconductor transition temperature T_c of the superconductive composition; and

(c) a current source causing an electric current to flow in the superconductor element.

166. (Added) An apparatus for conducting an electric current essentially without resistive losses, comprising:

(a) a superconductor element made of a superconductive composition, the superconductive composition consisting essentially of a copper-oxide compound having a layer-type perovskite-like crystal structure, the copper-oxide compound including at least one element selected from the group consisting of a Group II A element, a rare earth element and a Group III B

element, the composition having a superconductive/resistive transition defining a superconductive/resistive-transition temperature range between an upper limit defined by a transition-onset temperature T_c and a lower limit defined by an effectively-zero-bulk-resistivity intercept temperature $T_{p=0}$, the transition-onset temperature T_c being greater than 26°K;

Dep *sub* *9'*
(b) a temperature controller maintaining the superconductor element at a temperature below the effectively-zero-bulk-resistivity intercept temperature $T_{p=0}$ of the superconductive composition; and

(c) a current source causing an electric current to flow in the superconductor element.

167. (Added) An apparatus comprising:

a copper oxide having a phase therein which exhibits a superconducting state at a critical temperature in excess of 26°K;

Sh *ao*
a temperature controller maintaining the temperature of said material at a temperature less than said critical temperature to produce said superconducting state in said phase;

a current source passing an electrical supercurrent through said copper oxide while it is in said superconducting state;

said copper oxide includes at least one element selected from the group consisting of a Group II A element and at least one element

Added
selected from the group consisting of a rare earth element and a Group III B element.

168. (Added) An apparatus comprising:

Added
a composition including copper, oxygen and an element selected from the group consisting of at least one Group II A element and at least one element selected from the group consisting of a rare earth element and a Group III B element, where said composition is a mixed copper oxide having a non-stoichiometric amount of oxygen therein and exhibiting a superconducting state at a temperature greater than 26°K;

a temperature controller maintaining said composition in said superconducting state at a temperature greater than 26°K; and

Added
a current source passing an electrical current through said composition while said composition is in said superconducting state.

169. (Added) An apparatus comprising:

Added
a composition exhibiting a superconductive state at a temperature in excess of 26°K;

a temperature controller maintaining said composition at a temperature in excess of 26°K at which temperature said composition exhibits said superconductive state;

a current source passing an electrical current through said composition while said composition is in said superconductive state; and

said composition including a copper oxide and at least one element selected from the group consisting of Group II A and at least one element selected from the group consisting of a rare earth element and a Group III B element.

170. (Added) A superconductive apparatus for causing electric-current flow in a superconductive state at a temperature in excess of 26°K, comprising:

*JP
cred*

(a) a superconductor element made of a superconductive composition, the superconductive composition consisting essentially of a copper-oxide compound having a layer-type perovskite-like crystal structure, the composition having a superconductive transition temperature T_c of greater than 26°K, said superconductive composition includes at least one element selected from the group consisting of a Group II A element and at least one element selected from the group consisting of a rare earth element and a Group III B element;

*pub
3'*

(b) a temperature controller maintaining the superconductor element at a temperature above 26°K and below the superconductor transition temperature T_c of the superconductive composition; and

(c) a current source causing an electric current to flow in the superconductor element.

171. (Added) A superconductive apparatus for conducting an electric current essentially without resistive losses, comprising:

YO987-074BZ

SS
Cm
172
3'

(a) a superconductor element made of a superconductive composition, the superconductive composition consisting essentially of a copper-oxide compound having a layer-type perovskite-like crystal structure, the copper-oxide compound including at least one element selected from the group consisting of a Group II A element and at least one element selected from the group consisting of a rare earth element and a Group III B element, the composition having a superconductive/resistive transition defining a superconductive-resistive-transition temperature range between an upper limit defined by a transition-onset temperature T_c and a lower limit defined by an effectively-zero-bulk-resistivity intercept temperature $T_{p=0}$, the transition-onset temperature T_c being greater than 26°K;

(b) a temperature controller maintaining the superconductor element at a temperature below the effectively-zero-bulk-resistivity intercept temperature $T_{p=0}$ of the superconductive composition; and

(c) a current source causing an electric current to flow in the superconductor element.

172. (Added) An apparatus comprising:

a transition metal oxide having a phase therein which exhibits a superconducting state at a critical temperature in excess of 26°K;

a temperature controller maintaining the temperature of said material at a temperature less than said critical temperature to produce said superconducting state in said phase;

a current source passing an electrical supercurrent through said copper oxide while it is in said superconducting state;

Part 9
said transitional metal oxide includes at least one element selected from the group consisting of a Group II A element and at least one element selected from the group consisting of a rare earth element and a Group III B element.

173
173. (Added) An apparatus comprising:

Sub 173
a composition including a transition metal, oxygen and an element selected from the group consisting of at least one Group II A element and at least one element selected from the group consisting of a rare earth element and a Group III B element, where said composition is a mixed transitional metal oxide formed from said transition metal and said oxygen, said mixed transition metal oxide having a non-stoichiometric amount of oxygen therein and exhibiting a superconducting state at a temperature greater than 26°K;

a temperature controller maintaining said composition in said superconducting state at a temperature greater than 26°K; and

a current source passing an electrical current through said composition while said composition is in said superconducting state.

174. (Added) A method including the steps of:

forming a composition exhibiting a superconductive state at a temperature in excess of 26°K;

a temperature controller maintaining said composition at a temperature in excess of 26°K at which temperature said composition exhibits said superconductive state;

a current source passing an electrical current through said composition while said composition is in said superconductive state; and

41
D
C
said composition including a transitional metal oxide and at least one element selected from the group consisting of Group II A element and at least one element selected from the group consisting of a rare earth element and a Group III B element.

175. (Added) A superconductive apparatus for causing electric-current flow in a superconductive state at a temperature in excess of 26°K, comprising:

2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191

(b) a temperature controller maintaining the superconductor element at a temperature above 26°K and below the superconductor transition T_c of the superconductive composition; and

(c) a current source causing an electric current to flow in the superconductor element.

176. (Added) A superconductive apparatus for conducting an electric current essentially without resistive losses, comprising:

4/1 could
[Signature]
(a) a superconductor element made of a superconductive composition, the superconductive composition consisting essentially of a transition-metal-oxide compound having a layer-type perovskite-like crystal structure, the transition-metal-oxide compound including at least one element selected from the group consisting of a Group II A element and at least one element selected from the group consisting of a rare earth element and a Group III B element, the composition having a superconductive/resistive transition defining a superconductive/resistive-transition temperature range between an upper limit defined by a transition-onset temperature T_c and a lower limit defined by an effectively-zero-bulk-resistivity intercept temperature $T_{p=0}$, the transition-onset temperature T_c being greater than 26°K;

(b) a temperature controller maintaining the superconductor element at a temperature below the effectively-zero-bulk-resistivity intercept temperature $T_{p=0}$ of the superconductive composition; and

Sub 1
(c) a current source causing an electric current to flow in the superconductor element.

Sub 2
177. (Added) An apparatus comprising:

a copper oxide having a phase therein which exhibits a superconducting state at a critical temperature in excess of 26°K;

Sub 3
a temperature controller maintaining the temperature of said material at a temperature less than said critical temperature to produce said superconducting state in said phase;

a current source passing an electrical supercurrent through said copper oxide while it is in said superconducting state;

said copper oxide includes at least one element selected from group consisting of a Group II A element, ^{wherein composition} at least one element selected from the group consisting of a rare earth element and at least one element selected from the group consisting of a Group III B element.

112
clarify what is required by language

178. (Added) An apparatus comprising:

a composition including copper, oxygen and an element selected from the group consisting of at least one Group II A element and at least one element selected from the group consisting of a rare earth element at least one element selected from the group consisting of a Group III B element, where said composition is a mixed copper oxide having a non-stoichiometric amount of oxygen therein and exhibiting a superconducting state at a temperature greater than 26°K;

a temperature controller maintaining said composition in said superconducting state at a temperature greater than 26°K; and

a current source passing an electrical current through said composition while said composition is in said superconducting state.

179. (Added) A structure comprising:

Did
a composition exhibiting a superconductive state at a temperature in excess of 26°K;

a temperature controller maintaining said composition at a temperature in excess of 26°K at which temperature said composition exhibits said superconductive state;

*Sub
Add*
a current source passing an electrical current through said composition while said composition is in said superconductive state; and

said composition including a copper oxide and at least one element selected from the group consisting of Group II A element, at least one element selected from the group consisting of a rare earth element and at least one element selected from the group consisting of a Group III B element.

*1.2
c/sine
marks*

180. (Added) A superconductive apparatus for causing electric-current flow in a superconductive state at a temperature in excess of 26°K, comprising:

Sub 1
(a) a superconductor element made of a superconductive composition, the superconductive composition consisting essentially of a copper-oxide compound having a layer-type perovskite-like crystal structure, the composition having a superconductive transition temperature T_c of greater than 26°K, said superconductive composition includes at least one element selected from the group consisting of a Group II A element, at least one element selected from the group consisting of a rare earth element and at least one element selected from the group consisting of a Group III B element; *c (only)*

Sub 2
(b) a temperature controller maintaining the superconductor element at a temperature above 26°K and below the superconductor transition temperature T_c of the superconductive composition; and

(c) a current source causing an electric current to flow in the superconductor element.

181. (Added) A superconductive apparatus for conducting an electric current essentially without resistive losses, comprising:

c (only)
(a) a superconductor element made of a superconductive composition, the superconductive composition consisting essentially of a copper-oxide compound having a layer-type perovskite-like crystal structure, the copper-oxide compound including at least one element selected from the group consisting of a group II A element, at least one element selected from the group consisting of a rare earth element and at least one

element selected from the group consisting of a Group III B element, the composition having a superconductive-resistive transition defining a superconductive/resistive-transition temperature range between an upper limit defined by a transition-onset temperature T_c and a lower limit defined by an effectively-zero-bulk-resistivity intercept temperature $T_{p=0}$, the transition-onset temperature T_c being greater than 26°K;

(b) a temperature controller maintaining the superconductor element at a temperature below the effectively-zero-bulk-resistivity intercept temperature $T_{p=0}$ of the superconductive composition; and

(c) a current source causing an electric current to flow in the superconductor element.

182. (Added) An apparatus comprising providing a composition having a transition temperature greater than 26°K, the composition including a rare earth or alkaline earth element, a transition metal element capable of exhibiting multivalent states and oxygen, including at least one phase that exhibits superconductivity at temperature in excess of 26°K, a temperature controller maintaining said composition at said temperature to exhibit said superconductivity and a current source passing an electrical superconducting current through said composition with said phase exhibiting said superconductivity.

183. (Added) An apparatus comprising providing a superconducting transition metal oxide having a superconductive onset temperature greater than 26°K, a temperature controller maintaining said

*Sub
E18
C18*
superconducting transition metal oxide at a temperature less than said superconducting onset temperature and a current source flowing a superconducting current therein.

*Sub
C18
C18*
184. (Added) An apparatus comprising a superconducting copper oxide having a superconductive onset temperature greater than 26°K, a temperature controller maintaining said superconducting copper oxide at a temperature less than said superconducting onset temperature and a current source flowing a superconducting current in said superconducting oxide.

*Sub
C18
C18*
185. (Added) An apparatus comprising a superconducting oxide composition having a superconductive onset temperature greater than 26°K, a temperature controller maintaining said superconducting copper oxide at a temperature less than said superconducting onset temperature and a current source flowing a superconducting current therein, said composition comprising at least one each of rare earth, an alkaline earth, and copper.

*Sub
C18
C18*
186. (Added) An apparatus comprising a superconducting oxide composition having a superconductive onset temperature greater than 26°K, a temperature controller maintaining said superconducting copper oxide at a temperature less than said superconducting onset temperature and a current source flowing a superconducting electrical current therein, said composition comprising at least one each of a Group III B element, an alkaline earth, and copper.

*Sub
C18
C18*
187. (Added) An apparatus comprising ¹¹²flowing a superconducting electrical current in a transition metal oxide having a T_c greater than 26°K and maintaining said transition metal oxide at a temperature less than said T_c .

188. (Added) An apparatus comprising a current source flowing a superconducting current in a copper oxide having a T_c greater than 26°K and a temperature controller maintaining said copper oxide at a temperature less than said T_c .

189. (Added) An apparatus comprising the steps of:

*Did
add*

a composition of the formula $\text{Ba}_x\text{La}_{1-x}\text{Cu}_5\text{O}_y$, Cu_5O_y , wherein x is from about 0.75 to about 1 and y is the oxygen deficiency resulting from annealing said composition at temperatures from about 540°C to about 950°C and for times of about 15 minutes to about 12 hours, said composition having a metal oxide phase which exhibits a superconducting state at a critical temperature in excess of 26°K ;

*Sub
g'*

a temperature controller maintaining the temperature of said composition at a temperature less than said critical temperature to induce said superconducting state in said metal oxide phase; and

a current source passing an electrical current through said composition while said metal oxide phase is in said superconducting state.

190. (Added) An apparatus comprising a current source flowing a superconducting electrical current in a composition of matter having a T_c greater than 26°K , said composition comprising at least one each of a Group III B element, an alkaline earth, and copper oxide and a temperature controller maintaining said composition of matter at a temperature less than T_c .

191. (Added) An apparatus comprising a current source flowing a superconducting electrical current in a composition of matter having a T_c greater than 26°K , said composition comprising at least one each of a rare earth, alkaline earth, and copper oxide and a temperature controller maintaining said composition of matter at a temperature less than said T_c .

*Did
child*
192. (Added) An apparatus comprising a current source flowing a superconducting electrical current in a composition of matter having a T_c greater than 26°K , said composition comprising at least one each of a rare earth, and copper oxide and a temperature controller maintaining said composition of matter at a temperature less than said T_c .

*sub
g1*
193. (Added) An apparatus comprising a current source flowing a superconducting electrical current in a composition of matter having a T_c greater than 26°K carrying, said composition comprising at least one each of a Group III B element, and copper oxide and a temperature controller maintaining said composition of matter at a temperature less than said T_c .

194. (Added) An apparatus comprising a current source flowing a superconducting electrical current in a transition metal oxide comprising a $T_c > 26^\circ\text{K}$ and a temperature controller maintaining said transition metal oxide at a temperature less than said T_c .

195. (Added) An apparatus comprising a current source flowing a superconducting electrical current in a copper oxide composition of matter comprising a $T_c > 26^\circ\text{K}$ and a temperature controller maintaining said copper oxide composition of matter at a temperature less than said T_c .

196. (Added) An apparatus comprising:
YO987-074BZ

a composition including a transition metal, a Group III B element, an alkaline earth element, and oxygen, where said composition is a mixed transition metal oxide having a non-stoichiometric amount of oxygen therein and exhibiting a superconducting state at a temperature greater than 26°K,

a temperature controller maintaining said composition in said superconducting state at a temperature greater than 26°K, and

*Dep't
Aneld*
a current source passing an electrical current through said composition while said composition is in said superconducting state.

197. (Added) The apparatus of claim 196, where said transition metal is copper.

*Sub
3'*
198. (Added) A superconductive apparatus for causing electric current flow in a superconductive state at a temperature in excess of 26°K, comprising:

(a) a superconductor element made of a superconductive composition, the superconductive composition consisting essentially of a copper-oxide compound having a substantially layered perovskite crystal structure, the composition having a superconductor transition temperature T_c of greater than 26°K;

(b) a temperature controller maintaining the superconductor element at a temperature above 26°K and below the superconductor transition temperature T_c of the superconductive composition; and

(c) a current source causing an electric current to flow in the superconductor element.

199. (Added) The superconductive apparatus according to claim 198 in which the copper-oxide compound of the superconductive composition includes at least one element selected from the group consisting of a rare-earth element and a Group III B element and at least one alkaline-earth element. ¹¹² _{cl 199}

200. (Added) The superconductive apparatus according to claim 199 in which the rare-earth or rare-earth-like element is lanthanum.

201. (Added) The superconductive apparatus according to claim 199 in which the alkaline-earth element is barium.

202. (Added) The superconductive apparatus according to claim 198 in which the copper-oxide compound of the superconductive composition includes mixed valent copper ions.

203. (Added) The superconductive apparatus according to claim 202 in which the copper-oxide compound includes at least one element in a nonstoichiometric atomic proportion.

204. (Added) The superconductive apparatus according to claim 203 in which oxygen is present in the copper-oxide compound in a nonstoichiometric atomic proportion.

205. (Added) A superconductive apparatus for conducting an electric current essentially without resistive losses, comprising:

*Sub
C21
could*

(a) a superconductor element made of a superconductive composition, the superconductive composition consisting essentially of a copper-oxide compound having a substantially layered perovskite crystal structure, the copper-oxide compound including at least one element selected from the group consisting of a rare-earth element and a Group III B element and at least one alkaline-earth element, the composition having a superconductive/resistive transition defining a superconductive/resistive-transition temperature range between an upper limit defined by a transition-onset temperature T_c and a lower limit defined by an effectively-zero-bulk-resistivity intercept temperature $T_{p=0}$, the transition-onset temperature T_c being greater than 26°K;

(b) a temperature controller maintaining the superconductor element at a temperature below the effectively-zero-bulk-resistivity intercept temperature $T_{p=0}$ of the superconductive composition; and

(c) a current source causing an electric current to flow in the superconductor element.

206. (Added) The superconductive apparatus according to claim 205 in which said at least one element is lanthanum.

207. (Added) The superconductive apparatus according to claim 205 in which the alkaline-earth element is barium.

*Sub
C21
could*

208. (Added) The superconductive apparatus according to claim 205 in which the copper-oxide compound of the superconductive composition includes mixed valent copper ions.

209. (Added) The superconductive apparatus according to claim 208 in which the copper-oxide compound includes at least one element in a nonstoichiometric atomic proportion.

210. (Added) The superconductive apparatus according to claim 209 in which oxygen is present in the copper-oxide compound in a nonstoichiometric atomic proportion.

211. (Added) A superconductive apparatus for causing electric-current flow in a superconductive state at a temperature in excess of 26°K, comprising:

dy added
pub 3'
(a) a superconductor element made of a superconductive composition, the superconductive composition consisting essentially of a copper-oxide compound having a substantially layered perovskite crystal structure, the composition having a superconductive transition temperature T_c of greater than 26°K, said superconductive composition includes at least one element selected from the group consisting of a Group II A element, a rare earth element; and a Group III B element;

(b) a temperature controller maintaining the superconductor element at a temperature above 26°K and below the superconductor transition temperature T_c of the superconductive composition; and

(c) a current source causing an electric current to flow in the superconductor element.

212. (Added) A superconductive apparatus for conducting an electric current essentially without resistive losses, comprising:

*De
Inda*
*Pub
F'*
(a) a superconductor element made of a superconductive composition, the superconductive composition consisting essentially of a copper-oxide compound having a substantially layered perovskite crystal structure, the copper-oxide compound including at least one element selected from the group consisting of a Group II A element, a rare earth element and a Group III B element, the composition having a superconductive/resistive transition defining a superconductive/resistive-transition temperature range between an upper limit defined by a transition-onset temperature T_c and a lower limit defined by an effectively-zero-bulk-resistivity intercept temperature $T_{p=0}$, the transition-onset temperature T_c being greater than 26°K;

(b) a temperature controller maintaining the superconductor element at a temperature below the effectively-zero-bulk-resistivity intercept temperature $T_{p=0}$ of the superconductive composition; and

(c) a current source causing an electric current to flow in the superconductor element.

*Sub
E22*
213. (Added) A superconductive apparatus for causing electric-current flow in a superconductive state at a temperature in excess of 26°K, comprising:

*Sub
E2
Culd*

(a) a superconductor element made of a superconductive composition, the superconductive composition consisting essentially of a copper-oxide compound having a substantially layered perovskite crystal structure, the composition having a superconductive transition temperature T_c of greater than 26°K, said superconductive composition includes at least one element selected from the group consisting of a Group II A element and at least one element selected from the group consisting of a rare earth element and a Group III B element;

Class 1
213

*Sub
Culd*

(b) a temperature controller maintaining the superconductor element at a temperature above 26°K and below the superconductor transition temperature T_c of the superconductive composition; and

(c) a current source causing an electric current to flow in the superconductor element.

214. (Added) A superconductive apparatus for conducting an electric current essentially without resistive losses, comprising:

(a) a superconductor element made of a superconductive composition, the superconductive composition consisting essentially of a copper-oxide compound having a substantially layered perovskite crystal structure, the copper-oxide compound including at least one element selected from the group consisting of a Group II A element and at least one element selected from the group consisting of a rare earth element and a Group III B element, the composition having a

Class 1

superconductive/resistive transition defining a superconductive-resistive-transition temperature range between an upper limit defined by a transition-onset temperature T_c and a lower limit defined by an effectively-zero-bulk-resistivity intercept temperature $T_{p=0}$, the transition-onset temperature T_c being greater than 26°K;

(b) a temperature controller maintaining the superconductor element at a temperature below the effectively-zero-bulk-resistivity intercept temperature $T_{p=0}$ of the superconductive composition; and

(c) a current source causing an electric current to flow in the superconductor element.

215. (Added) A superconductive apparatus for causing electric-current flow in a superconductive state at a temperature in excess of 26°K, comprising:

(a) a superconductor element made of a superconductive composition, the superconductive composition consisting essentially of a transition metal oxide compound having a substantially layered perovskite crystal structure, the composition having a superconductive transition temperature T_c of greater than 26°K, said superconductive composition includes at least one element selected from the group consisting of a Group II A element and at least one element selected from the group consisting of a rare earth element and a Group III B element;

(b) a temperature controller maintaining the superconductor element at a temperature above 26°K and below the superconductor transition T_c of the superconductive composition; and

(c) a current source causing an electric current to flow in the superconductor element.

216. (Added) A superconductive apparatus for conducting an electric current essentially without resistive losses, comprising:

DE added
for 22 added
(a) a superconductor element made of a superconductive composition, the superconductive composition consisting essentially of a transition metal-oxide compound having a substantially layered perovskite crystal structure, the transition metal-oxide compound including at least one element selected from the group consisting of a Group II A element and at least one element selected from the group consisting of a rare earth element and a Group III B element, the composition having a superconductive/resistive transition defining a superconductive/resistive-transition temperature range between an upper limit defined by a transition-onset temperature T_c and a lower limit defined by an effectively-zero-bulk-resistivity intercept temperature $T_{p=0}$, the transition-onset temperature T_c being greater than 26°K;

c / n L

(b) a temperature controller maintaining the superconductor element at a temperature below the effectively-zero-bulk-resistivity intercept temperature $T_{p=0}$ of the superconductive composition; and

De
crack
(c) a current source causing an electric current to flow in the superconductor element.

217. (Added) An apparatus according to claim 182 wherein said composition comprises a substantially layered perovskite crystal structure.

218. (Added) An apparatus according to claim 183 wherein said superconducting transistor metal oxide comprises a substantially layered perovskite crystal structure.

De
crack
219. (Added) An apparatus according to claim 184 wherein said superconducting copper oxide comprises a substantially layered perovskite crystal structure.

220. (Added) An apparatus according to claim 185 wherein said superconducting oxide composition comprises a substantially layered perovskite crystal structure.

Pub
31
221. (Added) An apparatus according to claim 186 wherein said superconducting oxide composition comprises a substantially layered perovskite crystal structure.

222. (Added) An apparatus according to claim 187 wherein said transistor metal oxide comprises a substantially layered perovskite crystal structure.

223. (Added) An apparatus according to claim 188 wherein said copper oxide comprises a substantially layered perovskite crystal structure.

224. (Added) An apparatus according to claim 189 wherein said composition comprises a substantially layered perovskite crystal structure.

225. (Added) An apparatus according to claim 190 wherein said composition of matter comprises a substantially layered perovskite crystal structure.

226. (Added) An apparatus according to claim 191 wherein said composition of matter comprises substantially layered perovskite crystal structure.

227. (Added) An apparatus according to claim 192 wherein said composition of matter comprises a substantially layered perovskite crystal structure.

228. (Added) An apparatus according to claim 193 wherein said composition of matter comprises substantially layered perovskite crystal structure.

229. (Added) An apparatus according to claim 194 wherein said transistor metal oxide comprises substantially layered perovskite crystal structure.

230. (Added) An apparatus according to claim 195 wherein said copper oxide composition comprises substantially layered perovskite crystal structure.

REMARKS

Reconsideration is respectfully requested in view of any changes to the claims and the remarks herein. Please contact the undersigned to conduct a telephone interview in accordance with